

COUNTRY

Door Construction:	5 piece raised panel mortise and tenon construction.
Front Frame:	3/4" thick solid oak. 1-1/2" stiles and rails. Stiles and rails are dadoed to receive side panels.
Drawer Front:	Standard reveal flat panel drawer head.
Box Construction:	1/2" thick, plywood sides and full 1/8" back panel, finished interior.
Shelves:	3/4" thick, plywood. Fully adjustable in wall and base cabinets. Metal shelf clips standard.
Drawer Box:	1/2" thick plywood sides. 1/2" thick plywood bottom.
Butt Doors:	No center stile on 24" to 36" wide base cabinets. 39" to 48" will have a center stile.
Drawer Glides:	High quality epoxy coated steel side mount glides.
Hinges:	Heavy duty steel concealed hinge, four way adjustable.
Base Corner Braces:	High impact injection molded plastic.
Cabinet Assembly:	Cabinet is built utilizing the steal hardend interlock clips.
Upgrade:	<i>Dovetail undermount full extensions soft close.</i>

CONCORD

Door Construction:	Full overlay 5 piece raised panel mortise and tenon construction.
Front Frame:	3/4" thick solid wood. 1-1/2" stiles and rails. Stiles and rails are dadoed to receive side panels.
Drawer Front:	Full overlay 5 piece raised panel mortise and tenon construction.
Box Construction:	1/2" thick, plywood sides and full 1/2" back panel, finished interior with a natural birch wood veneer.
Shelves:	3/4" thick, plywood. Fully adjustable in wall and base cabinets. Metal shelf clips standard.
Drawer Box:	1/2" thick solid maple dovetail sides. 1/2" thick plywood bottom.
Butt Doors:	No center stile on 24" to 36" wide base cabinets. 39" to 48" will have a center stile.
Drawer Glides:	High quality epoxy coated steel under mount glides. Self adjusting.
Hinges:	Heavy duty steel concealed hinge, four way adjustable.
Base Corner Braces:	High impact injection molded plastic.
Cabinet Assembly:	Cabinet is constructed with high-strength fasteners, dadoed and glued at all key structural points.

CLASSIC

Door & Drawer:	Full overlay European Style.
Box Construction:	3/4" thick plywood sides, and a full 1/4" back panel with a 3/4" nailing strip for added installation support, finished interior with a natural birch wood veneer.
Shelves:	3/4" thick plywood. Fully adjustable in wall and base cabinets. Metal shelf clips standard.
Drawer Box:	5/8" thick Birch wood dovetail (Surell has a metal box).
Drawer Glides:	High quality steel, under mount, full extension Soft closing.
Hinges:	Heavy duty steel concealed hinge, four way adjustable.
Base Braces:	3/4" Front and back horizontal cross braces for maximum strength and a 4" back toe kick designed for added support.
Toe kick:	3/4" X 4" Toe kick.
Cabinet Assembly:	Cabinet is constructed with high-strength fasteners at all key structural points.